





C-GE-R-WD

Male stud connector (LL, L)

Male BSPP Thread with Captive seal (ISO 1179) /
24° Tube Connection (DIN EN ISO 8434-1)



C-GE-R-WD
(S)



Series	PN [bar]		ØD ₁ [mm]	T	ØD ₃ [mm]	ØD ₄ [mm]	L ₁ [mm]	L ₂ [mm]	L ₃ [mm]	L ₄ [mm]	S1 [mm]	S2 [mm]	Ordering Code *	kg/100
	C	CF												
LL	100	100	4	G1/8A	3	14	21.5	9.5	8	19.5	14	10	C-GE 04 LLR WD OMD	1.0
	100	100	6	G1/8A	4	14	21.5	8.0	8	19.5	14	12	C-GE 06 LLR WD OMD	1.1
L	315	315	6	G1/8A	4	14	23.5	8.5	8	23.5	14	14	C-GE 06 LR WD OMD	1.4
	315	500	6	G1/4A	4	19	29.0	10.0	12	25.0	19	14	C-GE 06 LR 1/4 WD OMD	3.0
	315	400	6	G3/8A	4	22	30.5	11.5	12	26.5	22	14	C-GE 06 LR 3/8 WD OMD	4.5
	315	400	6	G1/2A	4	27	33.0	12.0	14	27.0	27	14	C-GE 06 LR 1/2 WD OMD	6.0
	315	500	8	G1/4A	6	19	29.0	10.0	12	25.0	19	17	C-GE 08 LR WD OMD	2.7
	315	500	8	G1/8A	4	14	24.5	9.5	8	24.5	14	17	C-GE 08 LR 1/8 WD OMD	1.6
	315	400	8	G3/8A	6	22	30.5	11.5	12	26.5	22	17	C-GE 08 LR 3/8 WD OMD	4.7
	315	400	8	G1/2A	6	27	33.0	12.0	14	27.0	27	17	C-GE 08 LR 1/2 WD OMD	7.5
	315	500	10	G1/4A	6	19	30.0	11.0	12	26.0	19	19	C-GE 10 LR WD OMD	3.0
	315	315	10	G1/8A	4	14	25.5	10.5	8	25.5	17	19	C-GE 10 LR 1/8 WD OMD	2.2
	315	400	10	G3/8A	8	22	31.5	12.5	12	27.5	22	19	C-GE 10 LR 3/8 WD OMD	4.1
	315	400	10	G1/2A	8	27	34.0	13.0	14	28.0	27	19	C-GE 10 LR 1/2 WD OMD	5.2
	315	400	12	G3/8A	9	22	31.5	12.5	12	27.5	22	22	C-GE 12 LR WD OMD	4.1
	315	400	12	G1/8A	4	14	26.5	11.5	8	26.5	19	22	C-GE 12 LR 1/8 WD OMD	2.6
	315	400	12	G1/4A	6	19	31.0	12.0	12	27.0	19	22	C-GE 12 LR 1/4 WD OMD	3.0
	315	400	12	G1/2A	10	27	34.0	13.0	14	28.0	27	22	C-GE 12 LR 1/2 WD OMD	6.5
	160	250	12	G3/4A	10	32	37.0	14.0	16	29.0	32	22	C-GE 12 LR 3/4 WD OMD	11.9
	315	400	15	G1/2A	11	27	35.0	14.0	14	29.0	27	27	C-GE 15 LR WD OMD	7.1
	315	400	15	G3/8A	9	22	32.5	13.5	12	28.5	24	27	C-GE 15 LR 3/8 WD OMD	4.9
	160	250	15	G3/4A	12	32	38.0	15.0	16	30.0	32	27	C-GE 15 LR 3/4 WD OMD	12.0
	315	400	18	G1/2A	14	27	36.0	14.5	14	31.0	27	32	C-GE 18 LR WD OMD	7.0
	315	400	18	G3/8A	9	22	33.5	14.0	12	30.5	27	32	C-GE 18 LR 3/8 WD OMD	6.6
	160	250	18	G3/4A	15	32	38.0	14.5	16	31.0	32	32	C-GE 18 LR 3/4 WD OMD	13.4
	160	250	22	G3/4A	18	32	40.0	16.5	16	33.0	32	36	C-GE 22 LR WD OMD	10.4
	160	250	22	G1/2A	14	27	38.0	16.5	14	33.0	32	36	C-GE 22 LR 1/2 WD OMD	9.1
	160	250	22	G1A	19	40	43.0	17.5	18	34.0	41	36	C-GE 22 LR 1 WD OMD	19.0
	160	250	28	G1A	23	40	43.0	17.5	18	34.0	41	41	C-GE 28 LR WD OMD	16.5
	160	250	28	G3/4A	18	32	41.0	17.5	16	34.0	41	41	C-GE 28 LR 3/4 WD OMD	16.0
	160	250	28	G1 1/4A	24	50	46.0	18.5	20	35.0	50	41	C-GE 28 LR 1 1/4 WD OMD	26.2
	160	250	35	G1 1/4A	30	50	48.0	17.5	20	39.0	50	50	C-GE 35 LR WD OMD	27.5
	160	250	35	G1A	23	40	46.0	17.5	18	39.0	46	50	C-GE 35 LR 1 WD OMD	22.6
	160	250	35	G1 1/2A	30	55	52.0	19.5	22	41.0	55	50	C-GE 35 LR 1 1/2 WD OMD	42.0
	160	250	42	G1 1/2A	36	55	52.0	19.0	22	42.0	55	60	C-GE 42 LR WD OMD	34.5
	160	250	42	G1A	23	40	48.0	19.0	18	42.0	55	60	C-GE 42 LR 1 WD OMD	32.2
	160	250	42	G1 1/4A	30	50	50.0	19.0	20	42.0	55	60	C-GE 42 LR 1 1/4 WD OMD	34.0

*Replace the character "C" with "CF" when you require steel!
C = Stainless Steel, 1.4571 (Seal FKM) CF = Galvanized Steel Cr(VI)-free (Seal NBR)